

RECOIL REDUCING ACCESSORIES FOR FIREARMS

5

RELATION TO A COPENDING APPLICATION

10 This application is related to, and copending with, provisional application number
60/261,293 filed 11 January 2001. The benefit of the filing date of the provisional
application is claimed.

TECHNICAL FIELD OF THE INVENTION

15 In one respect the present invention relates to novel, improved devices (or
accessories) for reducing the recoil (or kick) of firearms which the shooter experiences
when a firearm is discharged by modifying the decay pattern of the vibrations set up in
the firearm when it is fired.

20 In another respect the present invention relates to accessories as defined in the
preceding paragraph which further reduce the kick experienced by the shooter by resilient
compression of an elastomeric component or by that mechanism and the pneumatic
compression of air in sealed pockets of the accessory.

BACKGROUND OF THE INVENTION

25 Shoulder-fired guns such as shotguns and rifles kick (i.e., recoil) when the gun is
fired. Particularly if the gun is one of larger caliber, or is fired automatically, or if a
round of wildcat or other ammunition of heavier charge is fired, the magnitude of the

recoil can be large enough to throw off the shooter's aim and can even lead to serious injury.

A variety of gunstock-mounted pads designed to mitigate this problem are commercially available, and many others are described in the patent literature and
 5 elsewhere. Previous solutions to the kick problem are less than satisfactory, in a major respect because they are not equipped to handle the particular type of vibrations set up in the stock when a gun is fired. Instead, their design is predicated on the erroneous assumption that "cushioning" is the best, if not the only, way of reducing recoil.

"Cushioning" devices are less than satisfactory because they do not focus on the
 10 phenomenon—impact—which is felt as a kick by the shooter when a firearm is discharged. Impact is a particular phenomenon in the general field of shock and vibration. An important characteristic of an impact is the presence of relatively large forces (or shock) at points of contact. In contrast to vibration, mechanical shock is of relatively short duration (a few milliseconds in the case of a firearm firing smokeless
 15 powder) and dies away rapidly. Cushioning, by itself, is not capable of dealing with these short duration, high magnitude shock vibrations to an extent necessary to provide the wanted reduction in kick or recoil.

The search for an effective recoil reducing firearm accessory continues.

SUMMARY OF THE INVENTION

20 Disclosed herein are novel recoil reducing accessories which modify the decay pattern and reduce the amplitude of the vibrations set up in its stock and transferable to

09070173 "05E501
 T050904700

the shooter as a kick when a gun is fired, particularly the sudden and high magnitude vibrations which characterize the shock generated when the firearm is discharged. The result is a marked decrease in the kick experienced by the shooter.

The novel recoil reducing accessories of the present invention have two complementary components. One is a pad which fits against the shoulder of the shooter and is fabricated from an elastomeric (or viscoelastic) material. The complementary component is a rigid plate to which one or more vibration pattern decay modifiers are attached.

These decay pattern modifiers are preferably of the character disclosed in U.S. patent No. 5,362,046. They have a mushroom-like configuration defined by a stem and an integral head. That end of the stem opposite the head of the decay pattern modifier is fixed to the butt-associated plate of the recoil reducing accessory and is configured for vibration in directions which encompass a 360 degree arc and are generally normal to the longitudinal axis of the decay pattern modifier. The head of the modifier is dimensioned and configured for free vibrational bending of its peripheral edge at all loci around the circumference thereof in first and second, opposite directions generally paralleling the longitudinal axis of the accessory. The free end of the (or each) decay pattern modifier - i.e., the end opposite the head-is attached to the plate of the component with an adhesive or in any other desired manner.

With the recoil reducing accessory assembled, each decay pattern modifier is seated in a recess or cavity formed in the elastomeric pad. These recesses are so dimensioned that the decay pattern modifier elements are free to move in and about the

03670178-033904
T06250-9/10/95

recesses in the manner discussed above. The result of the decay pattern modifier movement is a marked modification of the vibration decay pattern and a consequent reduction in the kick felt by the shooter.

Also, as the gun is discharged, the elastomeric pad of the accessory elastically compresses, thus cushioning the impact and further reducing the recoil felt by the shooter. Due to the material from which it is formed, the pad itself may also beneficially modify the decay pattern of the shock vibrations set up in the gunstock when the gun is fired.

In one currently preferred embodiment of the invention, those cavities in the elastomeric pad which house decay pattern modifiers are sealed when the plate of the accessory is assembled to the pad. As a consequence, the accessory also provides pneumatic cushioning by the compression of the air in such pockets when the firearm is discharged.

The modifier housing cavities (and others) in the elastomeric pad also "hollow out" the elastomeric, pad, increasing its compressibility and ability to reduce recoil.

Thus, accessories embodying the principles of the present invention may reduce the adverse effects experienced by the shooter when a firearm is discharged by mechanisms, including, but not necessarily limited to: (1) modification of the decay pattern of the shock vibrations set up in the gunstock when the gun is discharged; (2) reduction of the amplitude of those shock vibrations; (3) cushioning of the discharge-generated impact by compression of the elastically deformable accessory component, and (4) pneumatic cushioning by compression of the air in sealed pockets of the accessory. In

all devices embodying the principles of the invention, at least the first three of these mechanisms come into play and significantly reduce the kick felt by the shooter.

The novel accessories disclosed herein can, in different embodiments, be constructed for attachment to the end of a gunstock or so that they can be slipped onto the stock. They can be provided in versions which are customized for particular gunstocks
5 and versions which can be contoured to fit the stock after they have been installed.

The objects, features, and advantages of the present invention will be apparent to the reader from the foregoing and the appended claims and as the ensuing detailed description and discussion of the invention proceeds in conjunction with the
10 accompanying drawing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a pictorial view of a shooter holding a firearm equipped with a recoil reducing accessory embodying the principles of the present invention;

FIG. 2 is an exploded view of the recoil reducing accessory illustrated in FIG. 1;

15 FIG. 2A is an end view of the FIG. 1 accessory, showing that surface of an elastomeric accessory component which engages the shooter's shoulder;

FIG. 3 is a section through the recoil reducing accessory and that butt end of the gunstock to which the accessory is attached;

FIG. 3A is a fragment of FIG. 3, showing a very simplified pattern of the motions which a decay pattern modifier component of the FIG. 1 accessory manifests when a firearm equipped with the FIG. 1 accessory is fired;

FIG. 4 shows, in graphical form, the decay in frequency, over time, of the recoil generated and transmittable to the shooter when a 12 gauge shotgun equipped with a conventional gun butt pad was fired;

FIG. 5 is a graphic presentation similar to FIG. 4 but showing the marked reduction in recoil transmittable to the shooter when the same gun loaded with the same ammunition but with the accessory of FIG. 1 was fired;

FIG. 6 is an exploded view of a second accessory embodying the principles of the present invention and the butt end of the gunstock to which that accessory is attached;

FIG. 7 is a section through the FIG. 6 accessory and the butt end of the gunstock;

FIG. 8 is a fragment of FIG. 7, drawn to an enlarged scale to show how certain decay pattern modifying components of the FIG. 6 accessory function;

FIG. 9 is a view like FIG. 3A showing the character of motions of which a decay pattern modifier as shown in FIGS. 7 and 8 is capable;

FIG. 10 is a pictorial view of a third recoil reducing accessory embodying the principles of the present invention; this accessory is designed to be assembled to any one of a variety of gunstocks; this figure also shows a representative gunstock to which the accessory is attached;

FIG. 11 is similar to FIG. 12 but shows a rotary tool being employed to match the contour of the accessory to that of the gunstock;

FIG. 12 shows the gunstock and assembled accessory after the shaping operation is completed;

5 FIG. 13 is an exploded view of a fourth recoil reducing accessory embodying the principles of the present invention and the butt end of a gunstock; in this case, the accessory is designed to be installed by slipping it over the butt end of the gunstock; and

FIG. 14 is a perspective view of the FIG. 13 gunstock and installed accessory.

DETAILED DESCRIPTION OF THE INVENTION

10 Referring now to the drawings, FIG. 1 depicts a shooter 20 in the act of firing gun 22. Gun 22 is equipped with a recoil (or kick) reducing accessory 24 embodying the principles of the present invention. Accessory 24 is mounted to the butt end 26 of the gun's stock 28.

Turning next to FIGS. 2 and 3, accessory 24 comprises a generally rigid, plastic
15 or metal butt plate 30, an elastomeric pad 32, components 34 and 36 for modifying the decay pattern of the shock vibrations set up in stock 28 when gun 22 is fired, and double-adhesively-faced tabs 38 and 40 for attaching the vibration decay pattern modifying components 34 and 36 to accessory butt plate 30. The accessory 24 is attached to the butt end 26 of stock 28 by screws 42 and 44.

The butt plate 30 of accessory 24 has a flat base 46 which fits against the butt end 26 of gunstock 28, an integral side wall 49 extending around the periphery of base 48 and oriented at a right angle to that element, and a rim 50 which is integral with side wall 40 and extends around the periphery of the side wall at the edge thereof opposite the base.

5

Pad 32 can be fabricated from a variety of elastomeric materials. Preferred at the present time is the 522-2X material supplied by Oregon Rubber Company, Corvallis, Oregon. This material is a chloroprene polymer with a Durometer hardness of 20. Other elastomeric material with a Durometer hardness in the range of 12-30 can instead be employed, if desired.

10 Referring again to the drawings, elastomeric pad 32 has a monolithic element 51 and a second, integral element 52. Element 51 is contoured to complement the configuration of base plate rim 50.

Elements 51 and 52 define a ledge 53 extending around the periphery of pad 32. When the components of accessory 24 are assembled, elastomeric pad ledge 53 is seated on the rim 50 of accessory base plate 30. Pad element 52 extends into the cavity 54 defined by butt plate side wall 49, butts against base 46 of the butt plate, (see FIG. 3) and is surrounded by the butt plate side wall 49. This just described arrangement positively locates elastomeric pad 32 and base plate 30 relative to each other.

The exposed surface 56 of pad 32 has a convex shape in the transverse direction 58 with the same surface being concavely contoured in the longitudinal direction 60, falling off at toe 62, and tapering outwardly at heel 63 to conform surface 56 to the shoulder 64 of shooter 20.

Vibration decay pattern modifiers 34 and 36 are of like configuration, and both are fabricated of an elastomeric material, preferably that of which accessory pad 32 is made. The two accessory components 34 and 36 are of the mushroom-like configuration discussed above. This configuration is defined by a round head 65 (component 34) or 66 (component 36) and an integral, inline stem 68 (component 34) or 70 (component 36). Both the heads and the stems of the decay pattern modifiers have a circular cross-section.

Vibration decay pattern modifiers 34 and 36 are mounted to the base plate 30 of accessory 24 by the above-mentioned, adhesively faced tabs 38 and 40. These components are seated in complementary apertures 72 and 74 which are formed in the base 48 of accessory element 30 and are adhesively attached to the base.

The stems 68 and 70 of decay pattern modifiers 34 and 36 are then attached by the adhesive on the exposed sides of tabs 38 and 40. With the components 34 and 36 of accessory 24 assembled to butt plate 30, the heads 64 and 66 of those components fit in recesses 80 and 82. These recesses are formed in elastomeric accessory component 32 and open onto the surface 84 of that component.

The stems 68 and 70 of vibration decay pattern modifiers 34 and 36 can vibrate in directions generally normal to their longitudinal axes 80 and 82 (see arrows 85a and 85b, FIG. 3A) in any and all directions around the circumferences of the stems. At the same time, the peripheral edges 89 and 90 of decay pattern modifiers 34 and 36 can vibrate at loci around the circumferences of decay pattern modifier heads 84 and 86 in directions generally paralleling axis 86 and 88 (see arrows 90a and 90b, FIG. 3A). These several degrees of freedom of movement materially contribute to the effectiveness of accessory

24 in modifying the decay pattern of the shock vibration set up when gun 22 is fired as does the material from which the decay pattern modifiers are fabricated.

To accommodate the vibrations of components 34 and 36 just described for optimum effectiveness of accessory 24, the heads 65 and 66 of decay pattern modifiers 34 and 36 and the diameters of the cavities 72 and 74 in the elastomeric pad 32 are so relatively dimensioned that there is a gap (typically ca. one-sixteenth inch) between the decay pattern modifier head 65 or 66 and the companion elastomeric pad recess 72 or 74 around the circumference of the head (see arrows 91 and 92 in FIG. 3.) The width of this gap is, however, not critical; and it is acceptable if the vibrations of components of decay pattern modifiers of 34 and 36 cause them to touch elastomeric accessory pad 32 as they oscillate. This only causes energy to be transmitted to component 32 with a consequent, beneficial modification in the shock vibration decay pattern set up in stock 28 when gun 22 is fired.

Accessory 24 is assembled by first adhesively attaching shock vibration decay pattern modifiers 34 and 36 to accessory base plate 30 as described above. Next, the elastomeric pad component 32 of accessory 24 is assembled to base plate 30 with ledge 53 of the latter resting on rim 50 of the base plate, element 50 of the pad fitted in and surrounded by, side wall 52 of the base plate, the decay pattern modifying components 34 and 36 extending into elastomeric pad cavities 72 and 74, and the peripheral portions of the pad 32 and base plate 30 bonded together around their peripheral edges 93 by adhesive 92 (see FIG. 3). With this step completed, wall 46 of base plate 30 seals and isolates cavities 80 and 82.

Accessory 24 is fixed to the butt end 26 of gunstock 28 by installing fasteners 42 and 44 in apertures 94 and 96 in compressible accessory component 32 and then displacing the fasteners through apertures 98 and 100 in the base 48 of accessory base plate component 30. Next, the fasteners are threaded into apertures 102 and 104 in
5 gunstock 28 and tightened.

As discussed above, the recoil or kick felt by shooter 20 when firearm 22 is discharged is reduced by virtue of vibration decay modifying components 34 and 36 oscillating as discussed above. In addition, this decay pattern modification is supplemented to some extent by the decay pattern modifiers 34 and 36 and to a greater
10 extent by accessory component 32 due to the elastomeric properties of the material from which those components are fabricated.

Also, as mentioned above, kick is further reduced by the resilient compression of accessory component 32. In this regard, the cavities 80 and 82 which house decay pattern modifier heads 65 and 66 and cavities 106 and 108 in the path of threaded
15 fastener-receiving apertures 102 and 104 "hollow out" the interior of component 32, significantly increasing the compressibility of that elastomeric component. A further contribution to the compressibility of component 32 is made by the parallel, extended ridge-and-groove structure 110 extending around the periphery of component 32.

In addition to the kick reduction afforded by vibration decay pattern modification
20 and by the elastic compression of elastomeric component 32, the kick experienced by shooter 20 when firearm 22 is discharged is further reduced by the pneumatic

LOC

1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2

15

coil reducing access
ce character 120. Li
gid butt plate, an el
ern modifiers. This
teners. The butt plat
reference character 1
ters 130 and 132, an

In the FIGS. 6-9 embodiment of the invention, component 126 is a rigid flat plate configured to match the contour of gunstock butt end 122. Like the corresponding component 30 of accessory 24, butt plate 126 may be fabricated from any appropriate plastic or metal.

5 The elastomeric pad 128 has essentially the same peripheral configuration as butt plate 126. This component, like its counterpart 32 of accessory 24, is preferably, but not necessarily, fabricated from the elastomeric chloroprene polymer identified above.

Shock vibration decay pattern modifying components 130 and 132 are preferably made of the same chloroprene material. These components have heads 138 and 140 and
10 integral stems 142 and 144 with the stems being adhesively bonded or otherwise securely attached to butt plate 126.

With the butt plate 126 and elastomeric pad 128 of accessory 120 assembled (FIGS. 7 and 8), decay pattern modifiers 130 and 132 are situated in cavities 148 and 150 of elastomeric pad 128. These cavities open onto the butt plate-adjacent surface 152 of
15 the elastomeric pad and are dimensioned such that the decay pattern modifiers 130 and 132 have the freedom of movement discussed above in conjunction with the decay pattern modifiers 34 and 36 of accessory 24, (See the simplified motion pattern of FIG. 9 in which the wobbling motion of decay pattern modifier 130 about its longitudinal axis 155a is suggested by arrows 155b and 155c and the flip flop movements of the modifier
20 head peripheral edge 155d by arrows and 155e and 155f). Decay pattern modifier 132 exhibits a similar pattern of movement.

Referring now most particularly to FIG. 7, recoil reducing accessory 120 is installed by locating its rigid plate 126 on the butt end 122 of gunstock 124; placing the elastomeric pad 128 of the accessory on butt plate 126; displacing fasteners 135 and 136 through the elastomeric pad and the rigid plate; and then threading the fasteners into the butt end 122 of gunstock 124. The screws are tightened to hold the components of the accessory together and to secure the accessory to the gunstock.

Referring now specifically to FIG. 7, screw 135 is installed through an opening 157 in elastomeric pad 128 and an aperture 158 through butt plate 126; and screw 136 is similarly installed through an aperture 159 in elastomeric pad 128 and a through aperture 160 in the butt plate.

The holes in gunstock 124 into which the fasteners are threaded are identified by reference characters 162 and 164. As shown in FIG. 7, the heads 166 and 168 of the two fasteners 135 and 136 are seated on an elongated, metal or plastic mounting plate 170 molded into elastomeric pad 128 with the shanks 171a and 171b of fasteners 136 and 136 extending through apertures 171c and 171d in plate 170 (see FIG. 7). Plate 170 is employed because the elastomeric pad material is too soft to support screw heads 166 and 168. The screw heads would simply tear through the material as screws 135 and 136 were tightened, or, if they did not, the elasticity of the material would make it impossible to effect an unyielding connection between accessory 120 and gunstock 124; and the accessory would not function effectively, if at all. By using the mounting plate 170 and so positioning it in pad 128 that the plate butts against the butt end 122 of gunstock 124 (FIG. 7), the wanted rigid connection is made, while leaving pad 124 free to perform its vibration decay pattern modifying and cushioning functions.

Continuing still with FIG. 7, the screw accommodating apertures 157 and 159 in elastomeric pad 128 have a diameter much larger than is needed to accommodate fasteners 135 and 136; and a third cavity 172 of significant size is formed in elastomeric pad 128 in line with apertures 157 and 159. The three apertures or cavities just mentioned along with the cavities 148 and 150 in which the shock vibration decay pattern modifiers 130 and 132 are housed "hollow out" the elastomeric pad. This, like the comparable treatment of the accessory 20 elastomeric pad 32, increases the compressibility of the pad and, as a consequence, the cushioning effect of which that pad is capable.

10 Recoil reducing accessories of the character just discussed and illustrated in FIGS. 6-9 are designed to fit a particular gun butt. FIGS. 10-12 show another recoil reducing accessory of the same character as the one just described, but designed with a "one size fits all" approach in mind. This recoil reducing accessory is identified in the drawings by reference character 173; and, like the accessories described above, it has a rigid base or butt plate 174 and an elastomeric pad 175.

In this embodiment of the invention, the rigid butt plate 174 is dimensioned to overlap the butt end of the stock of any of a variety of guns to which accessory 170 might be attached with threaded fasteners (not shown) installed through elastomeric pad 175. Accessory 173 also has mushroom-shaped vibration decay pattern modifiers like those disclosed above and in the drawings and identified by reference characters 30, 32 and 130, 132. These components are hidden from view in FIGS. 10 - 12.

Once accessory 173 is fixed to gunstock 176, that peripheral portion 180 of butt plate 174 protruding beyond the contours of gunstock 176 is removed, typically with a rotary tool 182 shown schematically in FIG. 11. This leaves accessory 170 with its butt plate 174 matching the configuration of gunstock 176 as shown in FIG. 12.

5 The one size fits all innovation can also be used in accessories which are otherwise of the construction illustrated in FIGS. 1 – 3.

Yet another recoil reducing accessory used of the present invention is illustrated in FIGS. 13 and 14 and identified by reference character 190.

Accessory 190 has a rigid plate 192, decay pattern modifiers 194 and 196, and an
 10 elastomeric pad 198, all of the character discussed above in conjunction with FIGS. 1-3 and 6-9. This accessory also has a boot or sleeve 200 adhesively bonded or otherwise fixed to plate 192 on the side of that component opposite elastomeric pad 194.

Rather than being fastened to gunstock 202 with screws as in the previously described embodiments of the present invention, accessory 190 is installed by first
 15 stretching boot 200 as suggested by phantom line 201 in FIG. 13 and then sliding the butt end 202 of the gunstock into the open end 204 of the boot 202 as shown by arrow 206. The assembled accessory 190 and gunstock 192 are shown in FIG. 14.

Sleeve 196 is typically fabricated from the same elastomeric material as the elastomeric pad 198, in which case friction will securely keep the installed accessory 190
 20 in place on the gunstock.

The invention may be embodied in many forms without departing from the spirit or essential characteristics of the invention. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description; and all
5 changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

038701.3 038701.3